METAL TO WOOD FASTENERS

#10 WOODTITE®

HEAD
1/4" hex head

THREAD
Major Hi Diameter: .194"/.184"
Minor Diameter: .133"/.128"

POINT
Type-17 point

WASHER
Bonded Sealing Washer

MATERIAL
Carbon Steel

FINISH
Zinc Plated with corrosion resistant coating

PRODUCT SUPERIORITY

- Wet paint application for consistent socket fit and weathering performance
- Type-17 Point helps to penetrate metal more quickly while minimizing chips
- 26 Degree Sharp Point for quick piercing
- Can be painted industry standard colors

AVAILABLE SIZES

SIZE	ITEM #	BOX QTY
10-14 x 1	83639ZBN99XXHSL	3,000
10-14 x 1-1/2	83642ZBN99XXHSL	2,500
10-14 x 2	83644ZBN99XXHSL	2,000
10-14 x 2-1/2	83646ZBN99XXHSL	1,000
10-14 x 3	83648ZBN99XXHSL	1,000

STRENGTH CHARACTERISTICS

MINIMUM TORSIONAL	MINIMUM TENSILE	MINIMUM SHEAR	PULL OUT SPF2-1.5" PENETRATION	REVOLUTIONS/ IN.
68 in. lbs.	2,100 lbs.	1,265 lbs.	925 lbs.	7.0

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener. Actual field values may vary, therefore we assume no liability for use of this information. Pull out values are a measurement of material strength.

Installation Instructions - Do not use impact style guns. Use an electric screw gun with 2,500 RPM max.