ACCESSORIES

ULTIBOND®

Metal Roof Sealant

MADE IN USA

EASE OF USE

Fixed nozzle for easy application

Tack-free in less than one hour

DURABLE

Strong adhesion to galvinized, fluoropolymers, aluminum, stainless, laminates, glass, and vinyl

All-weather sealant

Highly mildew resistant

Flexible in low temps

Resistant to heat, cold, water, ozone and UV rays

PRODUCT SUPERIORITY

- Excellent cohesion strength after cure
- Available in translucent and industry standard colors
- Adheres to Aluminum, Steel, Galvalume, Painted Surfaces including Kynar
- Use for metal roof laps, trim, flashing, roof boots, gutters
- Made in the USA

Properties	Translucent Neutral Cure Silicone	Color Matched PolyEther
Tack Free Time	Less than 1 hour	Less than 1 hour
ASTM C920	Type S, Grade NS, Class 50 Use A,G, M, O	Type S, Grade NS, Use T, NT, I, G, A
Tensile Strength	341 psi	225 psi
Shear	122 psi	275 psi
Elongation	715%	275%
Service Temperature	-55 to 300 Degrees F	-75 to 300 (Intermittent) Degrees F
UV Resistance	Excellent	Excellent

*Testing substrate compatibility with any sealant before full application is recommended.